

IP-MT1526

15" Intel Atom™ N270 1.6GHz Medical PC with Bluetooth, WLAN and Battery



Features

- For eHealthcare or Bedside Entertainment System Application
- Low Power Intel Atom™ N270 1.6GHz
- Fanless Cooling System
- Front Panel IP54 Splashproof, Dust Resistant
- Dual Li-Battery (7,200mAh and 1880mAh) with Long Battery Life (5.5hrs)
- Multi-Connectivity (Bluetooth/WLAN/GbE LAN)
- Multi-Expansion (Mini-Card/Smart Card Reader)

System

CPU	Intel Atom™ N270 1.6GHz, FSB 533MHz/512K L2 Cache
Graphics Controller	Intel GMA950 Video Controller, up to 192MB shared memory
Memory	1 x 200-pin DDRII 667MHz SO-DIMM 1GB (Up to 2GB)
Chipset	Intel 945GSE + ICH7M
Serial ATA	1 x Serial ATA 300MB/s HDD transfer rate

Peripherals and Devices

Serial Port	2 x RS-232 ports
USB Port	4 x USB 2.0 ports
KB/MS	1 x PS2 K/B, 1 x Mouse
LAN	2 x Intel, WG82574L Gigabit LAN
VGA	1 x DB15 VGA port
Wi-Fi	1 x 802.11 b/g USB Wireless LAN Card with antenna (M1526/N270-F only)
Bluetooth	1 x Bluetooth module (M1526/N270-F only)
Smart Card Reader	1 x Smart Card Reader
CCD Camera	1 x 2.0 megapixel CMOS camera
Expansion Bus	1 x PCIe Mini-card (USB 2.0 or PCIe interface)

Switches

Function Keys	8 x programmable function keys (F1 – F8)
Warning LED	Programmable for function key
Power Button	On/Off
LED Indicator	3 x LEDs on front panel (Battery, Power, Storage)

Audio

Codec/Interface	Azalia HD Audio Codec (ALC888) Internal 2 x speakers (1.5W), Microphone built-in
------------------------	---

LCD Display

Size/Type	15 TFT Color LCD/1 Channel 24-bit LVDS
Max. Resolution	1024 x 768, XGA
Max. Colors	16.2M colors
Luminance	225 cd/m ²
Viewing Angle	130
Contrast Ratio	700 : 1
Backlight MTBF	30,000 hours

Touch Screen

Type	Analog Resistive
Light Transmission	80%
Controller Interface	USB Interface

Storage

HDD/Type	1 x 2.5" SATAII HDD bay
-----------------	-------------------------

Power Adapter & Battery

AC Input	100 ~ 240VAC (Full Range)
Frequency	47 ~ 63Hz
DC Output	65W (Max.), 3.5A/19VDC
Input Current (rms)	0.65A/100VAC, 0.27A/240VAC (Max.)
Battery	Dual Li-battery pack built-in (7200mAh and 1880mAh) (M1526/N270-F only)

Mechanical & Environmental

Operating Temp.	0 ~ 40°C (32 ~ 104°F)
Operating Humidity	5 ~ 85% (non-condensing)
Dimensions (W x D x H)	409 x 58 x 341 mm (16.1" x 2.28" x 13.43")
Vibration	17 to 500Hz, 1G PTP
Shock	10G/peak (11ms)
Construction	Plastic
Mounting	VESA-75/100 compatible
IP Rating	Front panel: IP54 splashproof, dust resistant
Certification	EMI, CE, FCC class-B, ROHS

Ordering Information

IP-MT1526-F	15" medical panel PC (gray) w/Intel Atom™ N270 1.6GHz CPU/80GB HDD/1GB RAM/Wireless LAN/Bluetooth/dual Batteries
IP-MT1526-A	15" medical panel PC (gray) w/Intel Atom™ N270 1.6GHz CPU/80GB HDD/1GB RAM/Wireless LAN/Bluetooth/single Battery
IP-MT1526-B	15" medical panel PC (gray) w/Intel Atom™ N270 1.6GHz/80GB HDD/1GB RAM
MTARM-150	VESA-75/100 desktop LCD monitor ARM

All specifications are subject to change without notice.